

COMBI DRILL

GSB 18V-21 Professional



PROFESSIONAL
18V
SYSTEM

55/21
Nm



Technical data

Part number	0 601 9H1 ...
Battery voltage	18 V
Torque (soft / hard / max.)	21 / 55 / · Nm
No-load speed (1st gear / 2nd gear)	0 – 480 / 0 – 1,800
Max. screw diameter	10 mm
Max. drilling diameter in wood	35 mm
Max. drilling diameter in masonry	11 mm
Max. drilling diameter in steel	10 mm
Weight excl. battery	1.2 kg

Comes complete with ... 175

2 x 2 Ah batteries	x
Quick charger GAL 18V-40 Professional (1 600 A01 9RJ)	x
L-BOXX 136 (1 600 A01 3G0)	x

DRILL DRIVER GSR 18V-28 Professional



Technical data	
Part number	0 601 9H4 ...
Battery voltage	18 V
Torque (soft / hard / max.)	28 / 63 / - Nm
No-load speed (1st gear / 2nd gear)	0 – 500 / 0 – 1,900 rpm
Max. screw diameter	8 mm
Max. drilling diameter in wood	38 mm
Max. drilling diameter in steel	13 mm
Weight excl. battery	1.1 kg
Comes complete with ... 100	
Body only	x
Cardboard box	x

DRILL DRIVER GSR 18V-45 Professional



Technical data	
Part number	0 601 9K3 ...
Battery voltage	18 V
Torque (soft / hard / max.)	21 / 45 / - Nm
No-load speed (1st gear / 2nd gear)	0 – 500 / 0 – 1,900 rpm
Max. screw diameter	8 mm
Max. drilling diameter in wood	35 mm
Max. drilling diameter in steel	10 mm
Weight excl. battery	0.9 kg
Comes complete with ... 200 ... 201	
Body only	x x
Cardboard box	x -
L-BOXX 136 (1 600 A01 2G0)	- x
L-BOXX inlay for tool	- x



GSB 18V-55 Professional



55/28
Nm



Technical data

Part number	0 601 9H5 ...
Battery voltage	18 V
Torque (soft / hard / max.)	28 / 55 / - Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,800 rpm
Max. screw diameter	10 mm
Max. drilling diameter in wood	35 mm
Max. drilling diameter in masonry	13 mm
Max. drilling diameter in steel	13 mm
Weight excl. battery	1.1 kg

Comes complete with ... 370

2 x battery GBA 18V 2.0Ah (1 600 Z00 036)	x
L-BOXX 136 (1 600 A01 2G0)	x
L-BOXX inlay for tool	x
Quick charger GAL 18V-40 Professional (1 600 A01 9RJ)	x

DRILL DRIVER

GSR 18V-60 C Professional



Technical data

Part number	0 601 9G1 ...
Battery voltage	18 V
Torque (soft / hard / max.)	31 / 60 / • Nm
No-load speed (1st gear / 2nd gear)	0 – 600 / 0 – 1,900 rpm
Max. screw diameter	10 mm
Max. drilling diameter in wood	38 mm
Max. drilling diameter in steel	13 mm
Weight excl. battery	1.2 kg

Comes complete with ... 173

2 x battery ProCORE18V 4.0Ah (1 600 A01 6GB)	x
L-BOXX 136 (1 600 A01 2G0)	x
Quick charger GAL 18V-40 Professional (1 600 A01 9RJ)	x

COMBI DRILL

GSB 18V-90 C Professional

NEW!



Technical data

Part number	0 601 9K6 ...
Battery voltage	18 V
Torque (soft / hard / max.)	36 / 64 / - Nm
No-load speed (1st gear / 2nd gear)	0 – 630 / 0 – 2,100 rpm
Max. screw diameter	12 mm
Max. drilling diameter in wood	68 mm
Max. drilling diameter in steel	13 mm
Weight excl. battery	1.2 kg

Comes complete with ... 171

2 x battery GBA 18V 4.0Ah (1 600 Z00 038)	x
Quick charger GAL 18V-40 Professional (1 600 A01 9RK)	x
L-BOXX 136 (1 600 A01 2G0)	x
L-BOXX inlay for tool (1 600 A02 K83)	x

GSB 18V-110 C Professional



Technical data

Part number	0 601 9G0 ...
Battery voltage	18 V
Torque (soft / hard / max.)	47 / 85 / 110 Nm
No-load speed (1st gear / 2nd gear)	0 – 480 / 0 – 2,100 rpm
Max. screw diameter	12 mm
Max. drilling diameter in wood	82 mm
Max. drilling diameter in masonry	16 mm
Max. drilling diameter in steel	13 mm
Weight excl. battery	1.5 kg

Comes complete with ... 376

2 x battery ProCORE18V 4.0Ah (1 600 A01 6GB)	x
Auxiliary handle (1 602 025 07X)	x
L-BOXX 136 (1 600 A01 2G0)	x
Quick charger GAL 18V-40 Professional (1 600 A01 9RJ)	x

COMBI DRILL

GSB 18V-150 C Professional



BITURBO
BRUSHLESS

Technical data

Part number	0 601 9J5 ...
Battery voltage	18 V
Torque (soft / hard / max.)	84 / 100 / 150 Nm
No-load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Max. screw diameter	13 mm
Max. drilling diameter in wood	150 mm
Max. drilling diameter in masonry	20 mm
Max. drilling diameter in steel	16 mm
Weight excl. battery	2.2 kg

Comes complete with

	... 101	... 172
1 x Bluetooth Low Energy module GCY 42 Professional (1 600 A01 3WF)	–	x
2 x battery ProCORE18V 8.0Ah (1 600 A01 93N)	–	x
Auxiliary handle (1 602 025 07Y)	x	x
Cardboard box	x	–
L-BOXX 136 (1 600 A01 2G0)	–	x
L-BOXX inlay for tool	–	x
Quick charger GAL 1880 CV (1 600 A00 B8H)	–	x

DRILL DRIVER

Bosch GO Professional



DUAL
ACTIVATION



ELECTRONIC
BRAKE



USB
CHARGER



TORQUE
SELECTION



TORQUE
SELECTION

Technical data

Part number	0 601 9H2 ...
Torque (soft / hard / max.)	2.5 / 5 / - Nm
No-load speed (1st gear / 2nd gear)	0 – 360 rpm
Max. screw diameter	5 mm

Comes complete with ... 170

25-piece screwdriver bit set	x
L-BOXX Mini (1 605 438 1GK)	x
Micro USB cable (1 607 000 CG9)	x
USB adapter (2 609 120 718)	x

DRILL DRIVER

GSR 12V-15 Professional



Technical data

Part number	0 601 868 ...
Battery voltage	12 V
Torque (soft / hard / max.)	15 / 30 / • Nm
No-load speed	0 – 400 rpm
Max. screw diameter	7 mm
Max. drilling diameter in wood	19 mm
Max. drilling diameter in masonry	10 mm
Max. drilling diameter in steel	10 mm
Weight excl. battery	1 kg

Comes complete with ... 17A

2 x 2.0Ah batteries	x
GAL 12V-2 charger	x
Tool bag	x

DRILL DRIVER

GSR 12V-15 FC Professional



Technical data

Part number	0-501 940 ...		
Battery voltage	12 V		
Torque (soft / hard / max.)	15 / 50 / 7 Nm		
Rotated speed (1st gear / 2nd gear)	0 - 400 / 0 - 1.300 rpm		
Max. screw diameter	7 mm		
Max. drilling diameter in wood	19 mm		
Max. drilling diameter in steel	10 mm		
Weight incl. battery	0.9 kg		
Comes complete with	... 500	... 578	... 571
1 x 15000 Inlay 12 V adapter (1 600 401 1090)	x	x	x
1 x 15000 Inlay for tool and charger (1 600 400 205)	x	x	x
2 x battery GSA 12V 2.0Ah (1 600 208 022)	--	x	x
Single adapter GSA 12V Professional (1 600 400 154)	--	x	--
Bit holder adapter GSA 12-V (1 600 400 752)	--	x	--
20° Check adapter GSA 12-V (1 600 400 154)	x	x	x
15000 100 (1 600 401 392)	x	x	x
15000 single adapter GSA 12-V (1 600 400 154)	x	x	--
Quick charger GSA 12V-60 Professional (1 600 401 084)	--	x	x

DRILL DRIVER

GSR 12V-35 FC Professional



1750
min/rpm

35/20
Nm



Technical data

Part number	0 601 9H3 ...
Battery voltage	12 V
Torque (soft / hard / max.)	20 / 35 / · Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Max. screw diameter	8 mm
Max. drilling diameter in wood	32 mm
Max. drilling diameter in steel	10 mm
Weight excl. battery	0.59 kg

Comes complete with

	... 002	... 003	... 004	... 00B
Angle adapter GFA 12-W Professional (1 600 A00 F5K)	–	x	–	–
Bit holder adapter GFA 12-X (1 600 A00 F5J)	–	x	–	–
Cardboard box	–	–	x	–
Drill chuck adapter GFA 12-B (1 600 A00 F5H)	x	x	–	–
L-BOXX 102 (1 600 A01 2FZ)	x	x	–	x
Offset angle adapter GFA 12-E (1 600 A00 F5L)	–	x	–	–
Auxiliary handle	–	–	–	x
Depth gauge	–	–	–	x
Rotary hammer attachment GFA 12-H (1 600 A02 4LN)	–	–	–	x
Drill chuck attachment GFA 12-B (1 600 A00 F5H)	–	–	–	x

COMBI DRILL

GSB 12V-35 Professional



Technical data

Part number	0 601 9J9 ...
Battery voltage	12 V
Torque (soft / hard / max.)	20 / 35 / • Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Max. screw diameter	8 mm
Max. drilling diameter in wood	32 mm
Max. drilling diameter in masonry	10 mm
Max. drilling diameter in steel	10 mm
Weight excl. battery	0.8 kg

Comes complete with ... 070

1 x belt clip, 1 x bit holder	x
1/2 L-BOXX inlay for accessories (1 600 A00 2WY)	x
1/2 L-BOXX inlay for tool and charger (1 600 A00 2V2)	x
2 x battery GBA 12V 3.0Ah (1 600 A00 X79)	x
L-BOXX 102 (1 600 A01 2FZ)	x
Quick charger GAL 12V-40 Professional (1 600 A01 9R4)	x