


ROTARY HAMMER WITH SDS PLUS

GBH 2-21 Professional



Technical data

Part number	0 611 2A6 ...
Rated input power	720 W
Impact energy	2 J
Impact rate at rated speed	0 – 4,800 bpm
Drilling dia. concrete, hammer drill bits	4 – 21 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm
Vibration level (drilling/chiselling)	11.9 m/s ²
Tool holder	SDS plus
Weight	2.3 kg


Comes complete with ... 071

1 x drill bit SDS plus, 10 mm (2 608 680 273)	x
1 x drill bit SDS plus, 8 mm (2 608 680 270)	x
1 x drill bit, SDS plus, 6 mm (2 608 680 263)	x
Auxiliary handle (1 619 P16 286)	x
Carrying case (1 619 P10 938)	x
Depth gauge (2 603 001 009)	x
Machine cloth (spare part number: 1 619 200 413)	x
Voltage 240 V	x

ROTARY HAMMERS, DEMOLITION HAMMERS, BREAKERS, CONCRETE NAILERS

ROTARY HAMMERS WITH SDS PLUS

ROTARY HAMMER WITH SDS PLUS GBH 2-21 Professional



Technical data	
Part number	0 611 2A6 ...
Rated input power	110 W
Impact energy	2 J
Impact rate at rated speed	0 – 4,800 bpm
Drilling dia. concrete, hammer drill bits	4 – 21 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm
Vibration level (drilling/chiselling)	11.9 m/s ²
Tool holder	SDS plus
Weight	2,3 kg
Comes complete with ... 061	
1 x drill bit SDS plus, 10 mm (2 608 680 273)	x
1 x drill bit SDS plus, 8 mm (2 608 680 270)	x
1 x drill bit, SDS plus, 6 mm (2 608 680 263)	x
Auxiliary handle (1 619 P16 286)	x
Carrying case (1 619 P10 938)	x
Depth gauge (2 603 001 009)	x
Machine cloth	x
(spare part number: 1 619 200 413)	
Voltage 110 V	x

ROTARY HAMMER WITH SDS PLUS GBH 2-26 Professional



Technical data		
Part number	0 611 2A3 ...	
Rated input power	830 W	
Impact energy	2.7 J	
Rated speed	0 – 900 rpm	
Impact rate at rated speed	0 – 4,000 bpm	
Drilling dia. concrete, hammer drill bits	4 – 26 mm	
Max. drilling diameter masonry, core cutters	68 mm	
Max. drilling diameter in metal	13 mm	
Max. drilling diameter in wood	30 mm	
Vibration level (drilling/chiselling)	17.5 / 14.0 m/s ²	
Tool holder	SDS plus	
Weight	2.7 kg	
Comes complete with ... 060 ... 070		
Auxiliary handle (2 602 025 141)	x	x
Carrying case	x	x
Depth stop 210 mm (1 613 001 010)	x	x
Machine cloth	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMER WITH SDS PLUS GBH 2-26 F Professional



Technical data		
Part number	0 611 2A4 ...	
Rated input power	830 W	
Impact energy	2.7 J	
Rated speed	0 – 900 rpm	
Impact rate at rated speed	0 – 4,000 bpm	
Drilling dia. concrete, hammer drill bits	4 – 26 mm	
Max. drilling diameter masonry, core cutters	68 mm	
Max. drilling diameter in metal	13 mm	
Max. drilling diameter in wood	30 mm	
Vibration level (drilling/chiselling)	16.5 / 14.0 m/s ²	
Tool holder	SDS plus	
Weight	2,9 kg	
Comes complete with ... 060 ... 070		
Auxiliary handle (2 602 025 141)	x	x
Carrying case	x	x
Depth stop 210 mm (1 613 001 010)	x	x
Machine cloth	x	x
Quick change chuck 13 mm (2 608 572 212)	x	x
SDS plus quick-change chuck (2 608 572 213)	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMER WITH SDS PLUS GBH 2-28 Professional



Technical data		
Part number	0 611 267 ...	
Rated input power	880 W	
Impact energy	3.2 J	
Rated speed	0 – 900 rpm	
Impact rate at rated speed	0 – 4,000 bpm	
Drilling dia. concrete, hammer drill bits	4 – 28 mm	
Max. drilling diameter masonry, core cutters	68 mm	
Max. drilling diameter in metal	13 mm	
Max. drilling diameter in wood	30 mm	
Vibration level (drilling/chiselling)	11.5 / 11.0 m/s ²	
Tool holder	SDS plus	
Weight	2,9 kg	
Comes complete with ... 561 ... 571		
Auxiliary handle (2 602 025 141)	x	x
Depth stop 210 mm (1 613 001 010)	x	x
L-BOXX 136 (1 600 A01 2G0)	x	x
L-BOXX inlay	x	x
Machine cloth	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMERS, DEMOLITION HAMMERS, BREAKERS, CONCRETE NAILERS

ROTARY HAMMERS WITH SDS PLUS, DUST COLLECTION COVER

ROTARY HAMMER WITH SDS PLUS GBH 2-28 F Professional



Technical data		
Part number	0 611 267 ...	
Rated input power	880 W	
Impact energy	3.2 J	
Rated speed	0 – 900 rpm	
Impact rate at rated speed	0 – 4,000 bpm	
Drilling dia. concrete, hammer drill bits	4 – 28 mm	
Max. drilling diameter masonry, core cutters	68 mm	
Max. drilling diameter in metal	13 mm	
Max. drilling diameter in wood	30 mm	
Vibration level (drilling/chiselling)	11.0 / 11.0 m/s ²	
Tool holder	SDS plus	
Weight	3.1 kg	
Comes complete with	... 661	... 671
Auxiliary handle (2 602 025 141)	x	x
Carrying case	–	x
Depth stop 210 mm (1 613 001 010)	x	x
L-BOXX 136 (1 600 A01 2G0)	x	–
L-BOXX inlay	x	–
Machine cloth	x	x
Quick change chuck 13 mm (2 608 572 212)	x	x
SDS plus quick-change chuck (2 608 572 213)	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMER WITH SDS PLUS GBH 3-28 DFR Professional



Technical data		
Part number	0 611 24A ...	
Rated input power	800 W	
Impact energy	3.1 J	
Rated speed	0 – 900 rpm	
Impact rate at rated speed	0 – 4,000 bpm	
Drilling dia. concrete, hammer drill bits	4 – 28 mm	
Max. drilling diameter masonry, core cutters	82 mm	
Max. drilling diameter in metal	13 mm	
Max. drilling diameter in wood	30 mm	
Vibration level (drilling/chiselling)	13.0 / 9.5 m/s ²	
Tool holder	SDS plus	
Weight	3.6 kg	
Comes complete with	... 060	... 070
Auxiliary handle (2 602 025 191)	x	x
Carrying case (2 605 438 651)	x	x
Depth stop 210 mm (1 613 001 010)	x	x
Quick change chuck 13 mm (2 608 572 212)	x	x
SDS plus quick-change chuck (2 608 572 213)	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMER WITH SDS PLUS GBH 4-32 DFR Professional



Technical data

Part number	0 611 332 ...
Rated input power	900 W
Impact energy	4.2 J
Rated speed	0 – 800 rpm
Impact rate at rated speed	0 – 3,600 bpm
Drilling dia. concrete, hammer drill bits	6 – 32 mm
Max. drilling diameter masonry, core cutters	90 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	32 mm
Vibration level (drilling/chiselling)	12.0 / 9.0 m/s ²
Tool holder	SDS plus
Weight	4.7 kg

Comes complete with

	... 161	... 171
Auxiliary handle (2 602 025 176)	x	x
Carrying case (2 605 438 651)	x	x
Depth stop 310 mm (1 613 001 003)	x	x
Quick change chuck 13 mm (2 608 572 212)	x	x
SDS plus quick-change chuck (2 608 572 213)	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMERS, DEMOLITION HAMMERS, BREAKERS, CONCRETE NAILERS

ROTARY HAMMERS WITH SDS MAX

ROTARY HAMMER WITH SDS MAX GBH 5-40 D Professional



Technical data	
Part number	0 611 269 ...
Rated input power	1,100 W
Impact energy	8.5 J
Rated speed	170 – 340 rpm
Impact rate at rated speed	1,500 – 2,900 bpm
Drilling dia. concrete, hammer drill bits	12 – 40 mm
Max. drilling diameter masonry, core cutters	90 mm
Vibration level (drilling/chiselling)	14.0 / 11.5 m/s ²
Tool holder	SDS max
Weight	6.8 kg
Comes complete with	... 060
Auxiliary handle (spare part number 1 602 250 07H)	x
Carrying case (spare part number 1 605 438 1D1)	x
Grease tube (spare part number 1 615 430 010)	x
Machine cloth (spare part number 1 619 200 413)	x
Voltage 110 V	x

ROTARY HAMMER WITH SDS MAX GBH 5-40 DCE Professional



Technical data		
Part number	0 611 264 ...	
Rated input power	1,150 W	
Impact energy	8.8 J	
Rated speed	170 – 340 rpm	
Impact rate at rated speed	1,500 – 3,050 bpm	
Drilling dia. concrete, hammer drill bits	12 – 40 mm	
Vibration level (drilling/chiselling)	10.5 / 7.5 m/s ²	
Tool holder	SDS max	
Weight	6.8 kg	
Comes complete with	... 060	... 070
Auxiliary handle (2 602 025 117)	x	x
Carrying case (spare part number 1 615 438 460)	x	x
Grease tube (spare part number 1 615 430 010)	x	x
Machine cloth	x	x
Voltage 110 V	x	–
Voltage 240 V	–	x

ROTARY HAMMER WITH SDS MAX GBH 8-45 D Professional



Technical data	
Part number	0 611 265 ...
Rated input power	1,500 W
Impact energy	12.5 J
Rated speed	150 – 305 rpm
Impact rate at rated speed	1,380 – 2,720 bpm
Drilling dia. concrete, hammer drill bits	12 – 45 mm
Max. drilling diameter masonry, core cutters	45 mm
Max. drilling diameter in metal	125 mm
Max. drilling diameter in wood	80 mm
Vibration level (drilling/chiselling)	18.5 / 14.0 m/s ²
Tool holder	SDS max
Weight	8.2 kg
Comes complete with	... 160
Auxiliary handle (spare part number 1 612 025 004)	x
Carrying case (spare part number 1 615 438 51A)	x
Grease tube (spare part number 1 615 430 010)	x
Machine cloth	x
Voltage 110 V	x

ROTARY HAMMER WITH SDS MAX GBH 8-45 DV Professional



Technical data	
Part number	0 611 265 ...
Rated input power	1,500 W
Impact energy	12.5 J
Rated speed	150 – 305 rpm
Impact rate at rated speed	1,380 – 2,760 bpm
Drilling dia. concrete, hammer drill bits	12 – 45 mm
Vibration level (drilling/chiselling)	8.0 / 7.0 m/s ²
Tool holder	SDS max
Weight	8.9 kg
Comes complete with	... 060
Auxiliary handle (spare part number 1 612 025 004)	x
Carrying case (spare part number 1 615 438 51A)	x
Grease tube (spare part number 1 615 430 010)	x
Machine cloth	x
Voltage 110 V	x

ROTARY HAMMERS, DEMOLITION HAMMERS, BREAKERS, CONCRETE NAILERS

ROTARY HAMMER WITH SDS MAX, DUST EXTRACTIONS WITH SDS MAX

ROTARY HAMMER WITH SDS MAX GBH 12-52 D Professional



Technical data	
Part number	0 611 266 ...
Rated input power	1,700 W
Impact energy	19 J
Rated speed	0 – 220 rpm
Impact rate at rated speed	1,750 – 2,150 bpm
Drilling dia. concrete, hammer drill bits	12 – 52 mm
Vibration level (drilling/chiselling)	20.0 / 15.0 m/s ²
Tool holder	SDS max
Weight	11.5 kg
Comes complete with ... 160	
Auxiliary handle (spare part number 1 612 025 004)	x
Carrying case (spare part number 1 615 438 705)	x
Grease tube (spare part number 1 615 430 010)	x
Machine cloth	x
Voltage 110 V	x
Voltage 240 V	–

ROTARY HAMMER WITH SDS MAX GBH 12-52 DV Professional



Technical data	
Part number	0 611 266 ...
Rated input power	1,700 W
Impact energy	19 J
Rated speed	0 – 220 rpm
Impact rate at rated speed	1,750 – 2,150 bpm
Drilling dia. concrete, hammer drill bits	12 – 52 mm
Vibration level (drilling/chiselling)	10.0 / 8.0 m/s ²
Tool holder	SDS max
Weight	11.9 kg
Comes complete with ... 060	
Auxiliary handle (spare part number 1 612 025 004)	x
Carrying case (spare part number 1 615 438 705)	x
Grease tube (spare part number 1 615 430 010)	x
Machine cloth	x
Voltage 110 V	x
Voltage 240 V	–