

CORDLESS SHEAR

GUS 12V-300 Professional



Technical data

| | |
|---------------------|---------------|
| Part number | 0 601 9B2 ... |
| Battery voltage | 12 V |
| No-load stroke rate | 700 spm |

Comes complete with ... 901

| | |
|---|---|
| Body only | x |
| 1/2 L-BOXX inlay for tool (1 600 A00 2W3) | x |
| Cardboard box | x |

CORDLESS SHEAR

GSC 18V-16 E Professional

NEW!



Technical data

| | |
|--|---------------|
| Part number | 0 601 926 ... |
| Battery voltage | 18 V |
| Cutting capacity in steel (400 N/mm ²), max. | 1.6 mm |
| Cutting capacity in steel (600 N/mm ²), max. | 1.2 mm |
| Cutting capacity in steel (800 N/mm ²), max. | 0.7 mm |
| Cutting capacity in aluminium (200 N/mm ²), max. | 2.2 mm |
| No-load stroke rate | 3,200 spm |
| Weight excl. battery | 1.6 kg |

Comes complete with ... 300

| | |
|---------------|---|
| Body only | x |
| Cardboard box | x |

CORDLESS SHEAR GSC 12V-13 Professional



Technical data

| | |
|--|---------------|
| Part number | 0 601 926 ... |
| Battery voltage | 12 V |
| Cutting capacity in steel (400 N/mm ²), max. | 1.3 mm |
| Cutting capacity in steel (600 N/mm ²), max. | 0.8 mm |
| Cutting capacity in steel (800 N/mm ²), max. | 0.6 mm |
| Cutting capacity in aluminium (200 N/mm ²), max. | 2.0 mm |

Comes complete with ... 105

| | |
|---|---|
| Body only | x |
| 1/2 L-BOXX inlay for tool (1 600 A00 2VD) | x |
| Cardboard box | x |
| Hex key | x |