

**DV36DC**

36V MultiVolt Brushless Combi Drill/Driver

- Industry's top class power and drilling speed to perform in the toughest applications
- Robust aluminium gear housing provides additional rigidity for the toughest applications
- Mechanical two-speed impact mechanism for highest performance and demands
- Reactive Force Control (RFC) technology and a gyro sensor detect when the tool bit



**Compatible**  
**BRUSHLESS**  
**RFC**

Specifications	
Battery Voltage	36V
Drill chuck	1,5-13mm keyless
Max. Brick	22mm
Max. Mild Steel	20mm
Max. Soft Wood	118mm
No load speed	0-550/min / 0-2200/min
Max. Torque (Hard / Soft Joint)	155Nm / 100Nm
Slip Torque Stages	22
Impact Rate	0 - 33000/min
Dimensions (LxWxH)	190 x 267 x 70mm
Weight	2,8kg with BSL36A18



**DV36DCJRZ**

2 x 5,0Ah Li-ion batteries + UC18YSL3 charger + side handle + belt hook + driver bit + HSC2

**DV36DCW2Z**

Body only + side handle + driver bit + belt hook + HSC2

**DV18DC**

18V Brushless Combi Drill/Driver

- Robust aluminium gear housing provides additional rigidity for the toughest applications
- Mechanical two-speed impact mechanism for highest performance and demands
- Reactive Force Control (RFC) technology and a gyro sensor detect when the tool bit is suddenly overburdened and stop the motor to reduce twisting of the main unit and to prevent potential injury

Specifications

Battery Voltage	18V
Drill chuck	1,5-13mm keyless
Max. Brick	20mm
Max. Metal	16mm
Max. Soft Wood	102mm
No load speed	0-500/min / 0-2000/min
Max. Torque (Hard / Soft Joint)	140Nm / 70Nm
Slip Torque Stages	22
Impact Rate	0 - 33000/min
Dimensions (LxWxH)	190 x 267 x 70mm
Weight	2,8kg with BSL36A18



**Compatible**  
**BRUSHLESS**  
**RFC**

**DV18DCJRZ**

2 x 5,0Ah Li-ion batteries + UC18YSL3 charger + side handle + belt hook + driver bit + HSC2

**DV18DCW2Z**

Body only + side handle + driver bit + belt hook + HSC2

**DV18DE**

18V Brushless Combi Drill/Driver

- High torque and high working speed to quickly perform tough applications
- Very short for optimum manoeuvrability and easy handling
- Reactive Force Control (RFC) stops the motor when the tool bit is suddenly overburdened to reduce twisting of the main unit and prevent potential injury

Specifications

Drill chuck	1,5 - 13mm keyless
Max. Wood	52mm
Max. Steel	13mm
Max. Masonry	13mm
Battery voltage	18V
No load speed	0-550/min / 0-2000/min
Impact rate	0-30000/min
Max. Torque (Hard)	70Nm
Overall length	159mm
Weight	1,9kg with BSL1850M



**Compatible**  
**BRUSHLESS**  
**RFC**

**DV18DEJFZ**

2 x BSL1850MA + UC18YSL3 Charger + driver bit + belt hook + HSC2

**DV18DEW2Z**

Body only + driver bit + belt hook + HSC2



**DS18DDQ**

18V Brushless Cordless 5-in-1 Drill Driver

- Driver Drill with Quick Attachment System enables easy attachment and removal of various attachments, such as chuck, bit holder and the angle and offset attachment.
- Quick and easy attachment swapping improves productivity and saves time.
- Removable attachments of the quick chuck system improve accuracy, especially in tight or hard-to-reach areas.
- Compact and lightweight 2-speed drill for easy handling.
- Tool length of only 165 mm and 116 mm without attachments for optimum manoeuvrability and easy handling.
- 13 mm chuck for a wide range of accessories.
- 20 adjustable torque settings for various applications.
- Ergonomic soft grip handle for optimal control and longer comfortable working.



**Compatible**  
**BRUSHLESS**



**DS18DDQJRZ**  
DS18DDQ Drill Driver  
379245, 379246, 379247, 379248  
2 x 2.0Ah Li-Ion Batteries (BSL120M)  
UC18YFSL Charger + HSC2

Specifications	
Max. capacity drilling	Steel 13 mm, Wood 36 mm
Max. capacity screwing	Wood screw 6 x 75 mm, Machine screw 6 mm
Capacity chuck	1,5 - 13 mm
Max. Torque	Hard 55 Nm, Soft 26Nm
No-load speed	Low mode 0 - 440 /min, High mode 0 - 1,700 /min
Slip torque	Stages 20, Torque 0,6- 4 Nm
LED light	YES
Center height offset attachment	11 mm
Dimensions: Without adapter	116 x 85 x 217 mm
with chuck	165 x 85 x 217 mm
with bit holder	160 x 85 x 217 mm
with offset adapter	200 x 85 x 217 mm
Weight	with BSL1820M 1,3 kg