



C3610DRA

36V Brushless MultiVolt 254mm Slide Compound Mitre Saw

- High efficiency brushless motor - long lifetime with reduced maintenance
- Batteries are compatible with existing Hitachi 18V tools
- Laser guide system for high cutting accuracy
- Compact slide system allows slide cuts with zero rear clearance

Compatible
BRUSHLESS



Specifications

Blade Diameter	255mm
Bore Ø	30mm
(HxW) Cross Cut: 0°	89 x 292mm
Mitre Cut: 45° L/R	89 x 204mm
Bevel Cut: 45° L	45 x 292mm
Bevel Cut: 45° R	25 x 292mm
Mitre Cut Angle:	Right 0-60° / Left 0-55°
Bevel Angle:	Right 0-48° / Left 0-48°
No load speed:	4000/min
Dimensions	778 x 792 x 686mm
Weight	20,6kg with BSL36B18

C3610DRAW4Z

Body only + + TCT saw blade 255mm 40T
(for wood cutting) (D30 hole with collar) + Dust bag
Vise assembly + Support rod ass'yx2 + 5 mm screwx2



C3612DRA

36V Brushless MultiVolt 305mm Slide Compound Mitre Saw

- **TORQUE BOOST TECHNOLOGY:** achieves remarkable balance between speed and precision in cutting tasks. This innovation ensures consistent performance, even when handling heavy loads, making it a reliable tool for various applications.
- **LED Shadow light:** provides users with the flexibility to achieve precise cuts. This feature allows for easy adjustment of the blade to the cut line, enhancing accuracy and contributing to the overall efficiency of the cutting process.
- **One-Touch Mitre Lock for Workflow Efficiency:** Streamlining the workflow, this saw offers the convenience of a one-touch mitre lock. This feature allows for quick and efficient adjustments, saving time and effort during tasks that require changes in cutting angles.
- **Metal Adjustable Scale for Durability and Accuracy:** Benefit from enhanced durability and accuracy with the metal adjustable scale. This component not only adds to the tool's robustness but also contributes to maintaining precise measurements, ensuring consistent & reliable results over time.
- **Front-Accessible Bevel & Mitre Lock:** Designed for practicality in narrow jobsites, this saw allows easy access to bevel and mitre locks from the front. This feature enhances maneuverability and accessibility, making the saw well-suited for confined spaces where traditional access might be challenging.



Specifications

Blade diameter	305mm Ø (12")
Maximum Cutting Capacity	0° : 107 x 312mm 45° (Bevel left): 70 x 312mm 45° (Bevel right): 45 x 312mm Mitre Left 45° + Bevel Left 45°: 70 x 220mm Mitre Left 45° + Bevel Right 45°: 45 x 265mm Mitre Right 45° + Bevel Right 45°: 45 x 220mm Mitre Right 45° + Bevel Left 45°: 70 x 265mm
Capacity	Mitre Angle: 0 – 45° (left) 0 – 57° (right) Bevel Angle: 0 – 45° (left) 0 – 45° (right)
No load speed	4,000 (min-1)
Blade bore	30 mm
Max. Torque (Hard/Soft)	140 Nm / 70 Nm
Dimensions (L x H x W)	873 x 916 x 724 mm
Weight	25.2 kg

C3612DRAW4Z

Body only + Dust bag + Vice assembly
8mm Hex bar wrench + Holder
TCT Saw blade 305mm Diameter 60Teeth

