

WR 25SE

25mm Impact Wrench



BRUSHLESS
AHB
ALUMINUM HOUSING BODY

Sq

25.4mm

Features

- Stable performance provided even at voltage drops
- Compatible with engine generators
- Bumper and Tail Bumper protect the tool body
- Soft grip handle
- Tumbler-type forward/reverse switch
- Hanger to hang on a rope

Specifications

Capacity: Ordinary Bolt	22 - 30mm
High Tension Bolt	22 - 24mm
Tightening Torque	1,000Nm
Square Drive	25.4mm
Power Input	900W
No Load Speed	1,100/min
Impact Rate	1,500/min
Overall Length	340mm
Weight*	8.4kg
Standard Accessories	Side Handle, Carrying Case



* Weight according to EPTA-Procedure 01/2014.

WR 16SE

16mm Impact Wrench



BRUSHLESS

Sq
12.7mm

Features

- Adjustable impact rate (tightening torque) with tightening mode change switch
- Compatible with engine generators
- Bumper protects the hammer case
- Tumbler-type forward/reverse switch
- With soft start and braking
- Soft grip handle
- Comes with hook

Specifications

Capacity: Ordinary Bolt	12 - 22mm
High Tension Bolt	12 - 16mm
Tightening Torque	360Nm
Square Drive	12.7mm
Power Input	370W
No Load Speed: Max	1,600/min
High	1,400/min
Mid	1,300/min
Lo	1,100/min
Impact Rate: Max	1,900/min
High	1,700/min
Mid	1,500/min
Lo	1,300/min
Overall Length	228mm
Weight*	2.6kg
Standard Accessories	Hook, Carrying Case



* Weight according to EPTA-Procedure 01/2014.

WR 14VE 14mm Impact Wrench

BRUSHLESS

Sq
12.7mm

Features

- Adjustable impact rate (tightening torque) with tightening mode change switch
- Compatible with engine generators
- Bumper protects the hammer case
- Electronic switch
- With soft start and braking
- Soft grip handle
- Comes with hook



Specifications

Capacity: Ordinary Bolt	10 - 18mm
High Tension Bolt	8 - 14mm
Tightening Torque	250Nm
Square Drive	12.7mm
Power Input	370W
No Load Speed: Max	0 - 2,100/min
High	0 - 1,800/min
Mid	0 - 1,600/min
Lo	0 - 1,400/min
Impact Rate: Max	0 - 2,700/min
High	0 - 2,300/min
Mid	0 - 1,900/min
Lo	0 - 1,500/min
Overall Length	210mm
Weight*	2.1kg
Standard Accessories	Hook, Carrying Case



* Weight according to EPTA-Procedure 01/2014.

WR 22SE

22mm Impact Wrench



BRUSHLESS
FHB
FLYING HOLE BOLT

Sq

19mm

Features

- Stable performance provided even at voltage drops
- Compatible with engine generators
- Bumper and Tail Bumper protect the tool body
- Soft grip handle
- Tumbler-type forward/reverse switch

Specifications

Capacity: Ordinary Bolt	14 - 24mm
High Tension Bolt	16 - 22mm
Tightening Torque	620Nm
Square Drive	19mm
Power Input	800W
No Load Speed	1,400/min
Impact Rate	2,000/min
Overall Length	280mm
Weight*	5.2kg
Standard Accessories	Side Handle, Carrying Case

* Weight according to EPTA-Procedure 01/2014.

