

C12RSH3

305mm Slide Compound Mitre Saw

NEW

- XACT CUT LED: Precise shadow cutting line without re-adjustment thanks to cleverly positioned LED
- Convenient bevel adjustment on the front
- Compact sliding system with double guides increases stability and prevents extension to the rear when working close to the wall
- The table can be extended on the right and the left for sawing wide workpieces
- Positive stops for fast and accurate mitre adjustments

Specifications

Blade Diameter / Bore Ø	305mm / Ø 30 mm
Bevel capacity	Left/right 0° - 45°
Mitre angle left	0° - 57°
Mitre angle right	0° - 45°
Cutting capacity (H x L)	0° 105 x 312 mm
	45° left 68 x 312 m
	45° right 43 x 312 m
	0° + mitre left 45° 105 x 220 mm
	0° + mitre right 45° 105 x 220 mm
	45° left + mitre l/r 45° 68 x 220 mm
	45° right + mitre l/r 45° 43 x 220 mm
Power Input	1520W
No Load Speed	4000/min
Double bevel	YES
Bevel lock on front	YES
Compact sliding system	YES
Shadow line	YES
Dimensions	655 x 873 x 724mm
Weight	25.5kg



C10FCE2

255mm Compound Mitre Saw

- Light weight for portability
- Pivoting sub fence
- Mitre cuts up to 52 degrees right & left
- Powerful 1520W motor
- Compound cuts up to 45 degrees



Specifications

Blade Diameter	255mm
Bore Ø	30mm
(H x W) Cross Cut 0°	59 x 144mm or 89 x 101mm
Mitre Cut 45°	65 x 220mm or 89 x 70mm
Bevel Cut 45°	41 x 144mm
Compound Mitre Cut 45° and bevel 45°	41 x 102mm
Power Input	1520W
No Load Speed	5000/min
Mitre Angle right/left	0 - 52° / 0 - 52°
Bevel Angle left	0 - 45°
Dimensions	460 x 628 x 561mm
Weight	11.5kg

C8FSE

216mm Slide Compound Mitre Saw

- 1050W motor
- Twin horizontal rails give a maximum cutting width of 312mm
- Left bevel cutting up to 48°
- 5 positive mitre stops at standard angles
- Lightweight design



Specifications

Blade Diameter / Bore Ø	216mm / Ø 30mm
(H x W) Cross Cut 0°	65 x 312mm
Mitre Cut 45°	65 x 220mm
Bevel Cut 45°	45 x 312mm
Compound Mitre Cut 45° and bevel 45°	45 x 220mm
Power Input	1050W
No Load Speed	5500/min
Mitre Angle right/left	0-57° / 0-45°
Bevel Angle right/left	0-5° / 0-48°
Dimensions	565 x 790 x 485mm
Weight	16.4kg