

DCJZ2050i (TYPE DM/Z)

20V-Cordless Brushless Driver/Hammer Drill

Tukul Pemutar Skru Bergerudi Tanpa Kord
充电式冲击螺丝起子电钻

- Type DM: 20V Max 2.0ah x1, 2A Charger
- Type Z: Solo

Group A
Product

Group B
Product



Max.Chucking Capacity Max. Kapasiti Chuck 夹头能力	13mm	
Rated Impact Frequency Kekerapan Kesan Dinilai 冲击数	0-27000 /min	
No-Load Speed Kelajuan Tanpa Beban 回转数	1st gear 2nd gear	0-550/min 0-1800/min
Max.Drilling Dia. Diameter Pengeboran Maksimum 最大钻孔直径	Steel Brick Wall Wood	Φ13mm Φ13mm Φ32mm
Torque Setting Tetapan Tork 扭矩设定	20+2	
Max.Torque Tenaga Maksimum 最大扭矩	50 N.m	
Net Weight Berat Bersih 净重	20V 2.0Ah 1.28kg	Solo 0.92kg

Work Amount Jumlah Kerja 工作量	Drill Bits & Screw Mata Bor dan Skru 10毫米扭转钻头	Material Bahan 材料	Quantity Kuantiti 数量	Time Masa 时间	
	10mm Twist Drill Bit Mata Pemutar 10mm 10毫米扭转钻头	3mm Square Tube 3mm 方管 Paip Persegi 3mm	80 holes 80 孔洞 80 Lubang	6s 1 hole 每6秒一个孔洞 1 lubang setiap 6 saat	
<i>*with a 20V 2.0Ah Fully Charged Battery</i> dengan bateri 20V 2.0Ah yang telah dicas sepenuhnya 使用已充满电的20V 2.0Ah 电池	10mm Twist Drill Bit Mata Pemutar 10mm 钻头和螺丝材料	40mm Thick Pine Wood 40mm Kayu Pine Tebal 40mm 厚松木	330 holes 330 孔洞 330 Lubang	1.3s 1 hole 每1.3秒一个孔洞 1 lubang setiap 1.3 saat	
	4.35 x 25mm Screw Skru 4.35 x 25mm 4.35 x 25毫米螺丝	Pine Wood 松木 Kayu Pine	1000 Pcs 1000 颗 1000 Biji	1.6s 1 hole 每1.6秒一个孔洞 1 lubang setiap 1.6 saat	
	20mm Carpentry Drill Pemutar Kayu 20mm 20毫米木工钻	40mm Thick Pine Wood 40mm Kayu Pine Tebal 40mm 厚松木	110 holes 110 孔洞 110 Lubang	8s 1 hole 每8秒一个孔洞 1 lubang setiap 8 saat	

DCJZ03-13 (TYPE EM/EK/Z)

20V-Cordless Brushless Driver/Hammer Drill

Tukul Pemutar Skru Bergerudi Tanpa Kord
充电式冲击螺丝起子电钻

- Type EM: 20V Max 4.0ah x2, 2A Charger
- Type EK: 20V Max 4.0ah x2, 4A Charger
- Type Z: Solo

Group B
Product

Group B
Product

Group B
Product



Max.Chucking Capacity Max. Kapasiti Chuck 夹头能力	13mm	
Max. Screw Dia. 最大螺钉直径 Saiz Sekrup Maksimum	10mm	
Rated Impact Frequency Kekerapan Kesan Dinilai 冲击数	0-32000/min	
No-Load Speed Kelajuan Tanpa Beban 回转数	1st gear 2nd gear	0-500/min 0-2000/min
Max.Drilling Dia. Diameter Pengeboran Maksimum 最大钻孔直径	Steel Brick Wall Wood	Φ13mm Φ13mm Φ45mm
Torque Setting Tetapan Tork 扭矩设定	24+2	
Max.Torque Tenaga Maksimum 最大扭矩	120 N.m	
Net Weight Berat Bersih 净重	20V 4.0Ah 2.2kg	Solo 1.6kg

Work Amount Jumlah Kerja 工作量	Drill Bits & Screw Mata Bor dan Skru 10毫米扭转钻头	Material Bahan 材料	Quantity Kuantiti 数量	
<i>*with a 20V 4.0Ah Fully Charged Battery</i> dengan bateri 20V 4.0Ah yang telah dicas sepenuhnya 使用已充满电的20V 4.0Ah 电池	ST6*505mm Wood Screw Skrup Kayu ST6*505mm ST6*505mm木螺丝	40mm Thick Pine Wood Kayu Pine Tebal 40mm 40mm厚松木	470 pcs 470 颗 470 Biji	
	10mm Sds Plus SDS Plus 10mm 10mm SDS Plus	40mm Cement Sand Brick Bata Simen Pasir 40mm 40mm水泥砂砖	90 holes 90 孔洞 90 Lubang	
	Φ35mm Saw Hole Lubang Gergaji Φ35mm 锯孔	40mm Thick Pine Wood Kayu Pine Tebal 40mm 40mm厚松木	110 holes 110 孔洞 110 Lubang	

DCJZ05-13 (TYPE EM/EK/Z)

20V-Cordless Brushless Driver/Hammer Drill

Tukul Pemutar Skru Bergerudi Tanpa Kord
充电式冲击螺丝起子电钻

- Type EM: 20V Max 4.0ah x2, 2A Charger
- Type EK: 20V Max 4.0ah x2, 4A Charger
- Type Z: Solo

Group B
Product

Group B
Product

Group B
Product



Max.Chucking Capacity Max. Kapasiti Chuck 夹头能力	13mm	
Max. Screw Dia. 最大螺钉直径 Saiz Sekrup Maksimum	10mm	
Rated Impact Frequency Kekerapan Kesan Dinilai 冲击数	0-36000/min	
No-Load Speed Kelajuan Tanpa Beban 回转数	1st gear 2nd gear	0-550/min 0-2000/min
Max.Drilling Dia. Diameter Pengeboran Maksimum 最大钻孔直径	Steel Brick Wall Wood	Φ13mm Φ13mm Φ38mm
Torque Setting Tetapan Tork 扭矩设定	22+2	
Max.Torque Tenaga Maksimum 最大扭矩	60 N.m	
Net Weight Berat Bersih 净重	20V 4.0Ah 1.9kg	Solo 1.3kg

DCJZ1202i (TYPE TD)

20V-Cordless Driver/Hammer Drill Combo Kit

Pakej Kombinasi Tukul Pemutar Skru Bergerudi Tanpa Kord

充电式冲击螺丝起子电钻配套

• Type TD: 12V 2.0ah x2, 1.3A Charger

Group A Product



Max.Chucking Capacity Max. Kapasiti Chuck 夹头能力	10mm	
Max. Screw Dia. 最大螺钉直径 Saiz Sekrup Maksimum	6mm	
Impact Frequency Kekerapan Kesan Dinilai 冲击数	Low High	0-6000/min 0-22500/min
No-Load Speed Kelajuan Tanpa Beban 回转数	Low High	0-400/min 0-1500/min
Max. Drilling Dia. Diameter Pengeboran Maksimum 最大钻孔直径	Steel Stone Wood	Φ10mm Φ8mm Φ22mm
Torque Setting Tetapan Tork 扭矩设定	18+2	
Max. Torque Tenaga Maksimum 最大扭矩	35 N.m	
Net Weight Berat Bersih 净重	1.0kg	

DCJZ23-10i (TYPE EK) Steel

12V-Cordless Brushless Driver/ Hammer Drill

Gerudi Pemutar Skru Tanpa Kord
充电式螺丝起子电钻

• Type EK: 12V 2.0ah x2, 3.0A Charger

Group A Product



Max.Chucking Capacity Max. Kapasiti Chuck 夹头能力	10mm	
Max. Screw Dia. 最大螺钉直径 Saiz Sekrup Maksimum	7mm	
Impact Frequency Kekerapan Kesan Dinilai 冲击数	0-24000/min	
No-Load Speed Kelajuan Tanpa Beban 回转数	Low High	0-460/min 0-1600/min
Max. Drilling Dia. Diameter Pengeboran Maksimum 最大钻孔直径	Steel Brick Wall Wood	Φ10mm Φ8mm Φ20mm
Torque Setting Tetapan Tork 扭矩设定	20+2	
Max. Torque Tenaga Maksimum 最大扭矩	35 N.m	
Net Weight Berat Bersih 净重	1.0kg	

DCPL04-8 (TYPE EK/Z)

12V-Cordless Brushless Impact Driver

Pemutar Skru Impak Tanpa Kord
充电式冲击螺丝起子机

• Type EK: 12V 2.0ah x2, 3.0A Charger

• Type Z: Solo



Standard Bolt Size Saiz Bolt Piawai 标准螺栓尺寸	M5-M14	
Clamping Capacity Kapasiti Penjepitan 夹紧能力	6.35mm Hex	
No-Load Speed Kelajuan Tanpa Beban 回转数	Low High	0-1200/min 0-3300/min
Rated Impact Impak Dinilai 额定冲击次数	Low High	0-1600/min 0-4000/min
Max. Fastening Torque 最大扭矩 Maksimum Tenaga Pemutaran Pengancing	140N.m	
Net Weight Berat Bersih 净重	12V 2.0Ah 0.9kg	Solo 0.7kg