

# INVERTER GENERATOR

## LIGHT WEIGHT SERIES

### Performance characteristics



• Maintenance-free within 100 hours.




• Ultra quiet, low noise level.



• Size smaller and light weight ,loading Q'ty more than standard.



• Cost effective.



Parallel Operation  
Function (Optional)



SC1400i

SC2000i(D)

SC3500i(D)

SC4500i(D)

SC6000i(D)

(D) Means dual fuel optional



Model	SC1400i	SC2000i(D)	SC3500i(D)	SC4500i(D)	SC6000i(D)
Frequency	50Hz / 60Hz				
Rated power	1.2kW	1.8kW	3.0kW	4.0kW	5.5kW
Max. power	1.3 kW	2.0kW	3.5kW	4.5kW	6.0kW
AC voltage	120V/240V				
Phase	Single				
Fuel capacity	2.5L	3.0L	6.0L	10.0L	13.5L
Run time (50%-100% load)	4.5 - 2.5h	5 - 3h	5.5 - 3.5h	9.5-4.5h	11- 4.5h
Engine model	SH60C(60cc)	SH80C(80cc)	SH150B(149cc)	SH230B(224cc)	SV320B(322cc)
Start system	Recoil	Recoil	Recoil/E-start	Recoil/E-start	Recoil/E-start
Noise level (@1/4 load, 7m)	59dB	62dB	62dB	62dB	64dB
Parallel ready	Yes				
Dimensions(mm)	430*252*400	505*272*470	500*309*469	541*396*505	610*430*535
Net weight	12kg	15.1kg	24.5kg	39kg	59.2kg
Loading Q'ty (20GP/40HQ)	384/1230	288/720	240/512	126/336	96/264