

INVERTER GENERATOR

SUPER QUIET SERIES

Performance characteristics



• Inverter technology for clean power, THD<3%.




• Ultra quiet, low noise level.



• Economy system, electronic speed control function, low fuel consumption.



• Light and portable.



Parallel Operation Function (Optional)



Gas LPG
Your Choice!



SC2000i(D)

SC2300i-HT(D)

SC2300i-O(D)

SC4000i-O(D)

(D) Means dual fuel optional

Model	SC2000i(D)	SC2300i-HT(D)	SC2300i-O(D)	SC4000i-O(D)
Frequency	50Hz / 60Hz	50Hz / 60Hz	50Hz / 60Hz	50Hz / 60Hz
Rated power	1.6kW	1.8kW	1.8kW	3.5kW
Max. power	2.0kW	2.3kW	2.3kW	4.0kW
AC voltage	120V/240V	120V/240V	120V/240V	120V/240V
Phase	Single	Single	Single	Single
Fuel capacity	4.0L	4.2L	4.0L	10L
Run time (50%-100% load)	6.5 - 4h	5.5 - 4h	5.5 - 4h	9.0 - 5.5h
Engine model	SC80 (80cc)	SC80 (80cc)	SC80 (80cc)	SV230 (223cc)
Start system	Recoil	Recoil start	Recoil start	Recoil/E-start
Noise level (@1/4 load, 7m)	60dB	63dB	63dB	58dB
Parallel ready	Yes	Yes	Yes	Yes
Dimensions(mm)	530*315*490	560*360*530	560*360*530	660*560*650
Net weight	22kg	23kg	23kg	51kg
Loading Q'ty (20GP/40HQ)	272/560	240/496	240/496	128/280

INVERTER GENERATOR

SUPER QUIET SERIES

Performance characteristics



• Inverter technology for clean power, THD<3%.



• Ultra quiet, low noise level.



• Economy system, electronic speed control function, low fuel consumption.



• Light and portable.



Gas LPG
Your Choice!



Parallel Operation Function (Optional)



SC2300i-BF

SC3500iBC(D)

(D)Means dual fuel optional



Model	SC2300i-BF	SC3500iBC(D)
Frequency	50Hz / 60Hz	50Hz / 60Hz
Rated power	2.0kW	3.0kW
Max. power	2.2kW	3.5kW
AC voltage	120V/240V	120V/240V
Phase	Single	Single
Fuel capacity	4L	6L
Run time (50%-100% load)	5.5 - 4h	6 - 4h
Engine model	SH100B(98cc)	SH160B(161cc)
Start system	Recoil start	Recoil/E-start
Noise level (@1/4 load, 7m)	59dB	62dB
Parallel ready	Yes	Yes
Dimensions(mm)	515*310*490	610*385*540
Net weight	18.5kg	28kg
Loading Q'ty (20GP/40HQ)	272/720	132/368